

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) Issue date: 1/20/2025 Version: 1.0

#### **SECTION 1 Identification**

#### 1.1. Product identifier

Product form : Mixture

Product name : SureKill® Advanced Insecticide Products VAP-5™

Product code : 0744010

#### 1.2. Other means of identification

Part Number(s) : 0744010

#### 1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Insecticide

Restrictions on use : RESTRICTED USE PESTICIDE: For retail sale to and use only by certified applicators or

persons under their direct supervision and only for those uses covered by the certified

applicator's certification.

#### 1.4. Supplier's details

#### Supplier

Neogen Corporation 620 Lesher Place Lansing, Michigan 48912 United States of America

T 800.234.5333

sds@neogen.com - https://www.neogen.com/

#### Manufacturer

Chem-Tech, Ltd., a Neogen Company

1006 Business Highway 5 Pleasantville, Iowa 50225

U.S.A.

#### 1.5. Emergency phone number

Emergency number : 24 hours:

Medical: 1-800-498-5743 (U.S. and Canada) or 1-651-523-0318 (international)

Spill/CHEMTREC: 1-800-424-9300 (U.S. and Canada) or 1-703-527-3887 (international)

## **SECTION 2 Hazard Identification**

## 2.1. Classification of the substance or mixture

### GHS US classification

Flammable liquid, Category 3	H226	Flammable liquid and vapor.
Acute toxicity (oral), Category 4	H302	Harmful if swallowed.
Acute toxicity (dermal), Category 4	H312	Harmful in contact with skin.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351	Suspected of causing cancer.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.

Hazardous to the aquatic environment — Acute Hazard, Category 1 H400 Very toxic to aquatic life. Full text of H statements : see section 16

1/20/2025 (Issue date) US - en 1/13

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

#### 2.2. Label elements

#### **GHS US labeling**

Hazard pictograms (GHS US)









Signal word (GHS US)

Hazard statements (GHS US)

: Danger

H226 - Flammable liquid and vapor

H302+H312 - Harmful if swallowed or in contact with skin H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H336 - May cause drowsiness or dizziness H351 - Suspected of causing cancer.

H400 - Very toxic to aquatic life

Precautionary statements (GHS US)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves.

P301+P310 - If swallowed: Immediately call a poison center or doctor.

P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P312 - Call a poison center or doctor if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P330 - Rinse mouth.

P331 - Do NOT induce vomiting.

P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use appropriate media to extinguish.

P391 - Collect spillage.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

1/20/2025 (Issue date) US - en 2/13

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

#### 2.4. Hazards not otherwise classified

Other hazards which do not result in classification : Read the entire label and follow all use directions, restrictions,

and precautions.

#### 2.5. Unknown acute toxicity

No additional information available

### **SECTION 3 Composition/information on ingredients**

#### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Kerosene (straight run)	CAS-No.: 8008-20-6	≥ 75	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304
Dichlorvos	CAS-No.: 62-73-7	5 – 10	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330 Skin Sens. 1, H317 Carc. 2, H351 Aquatic Acute 1, H400 (M=10000)

Full text of hazard classes and H-statements : see section 16

## **SECTION 4 First aid measures**

#### 4.1. Description of necessary first-aid measures

First-aid measures general : Call a physician immediately. Refer to product label and/or package insert for additional

information. Follow label instructions.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin

irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : Harmful in contact with skin. Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : None under normal conditions.

Symptoms/effects after ingestion : Harmful if swallowed. Risk of lung edema.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

1/20/2025 (Issue date) US - en 3/13

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

#### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

#### **SECTION 6 Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb

spillage to prevent material-damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

Environmental precautions : Avoid release to the environment.

#### 6.2. Methods and materials for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into

sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

1/20/2025 (Issue date) US - en 4/13

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

#### **SECTION 7 Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the

container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood. Use only outdoors or in a well-ventilated area. Avoid breathing

dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Refer to product

label and/or package insert for additional information. Follow label instructions.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed

out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

#### 7.2. Conditions for safe storage, including incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Packaging materials : Store always product in container of same material as original container.

#### **SECTION 8 Exposure controls/personal protection**

#### 8.1. Control parameters

Dichlorvos (62-73-7)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Dichlorvos	
ACGIH® TLV® TWA	0.1 mg/m³ (Inhalable fraction and vapor)	
	0.01 ppm (IFV - Inhalable fraction and vapor)	
Remark (ACGIH)	TLV® Basis: Cholinesterase inhib. Notations: Skin; DSEN; A4 (Not classifiable as a Human Carcinogen); BEIc	
Regulatory reference	ACGIH 2025	
USA - OSHA - Occupational Exposure Limits		
Local name	Dichlorvos (DDVP)	
OSHA PEL TWA	1 mg/m³	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
USA - Cal/OSHA - Occupational Exposure Limits		
Local name	Dichlorvos (DDVP); 2,2-dichlorovinyl dimethyl phosphate	
Cal/OSHA PEL (OEL TWA)	1 mg/m³	
	0.1 ppm	
Remark (Cal/OSHA)	S - Skin notation and Protecting Clothing	
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)	
USA - NIOSH - Occupational Exposure Limits		
Local name	Dichlorvos (DDVP)	

1/20/2025 (Issue date) US - en 5/13

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Dichlorvos (62-73-7)		
NIOSH REL 10h TWA	1 mg/m³	
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))	
Kerosene (straight run) (8008-20-6)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Kerosene, as total hydrocarbon vapor	
ACGIH® TLV® TWA	200 mg/m³ (Application restricted to conditions in which there are negligible aerosol exposures)	
Remark (ACGIH)	TLV® Basis: Skin & URT irr; CNS impair. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)	
Regulatory reference	ACGIH 2024	

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

Hand	protection:
------	-------------

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):







#### Other information:

Refer to product label for additional PPE requirements and recommendations. Follow label instructions.

## **SECTION 9 Physical and chemical properties**

#### 9.1. Basic physical and chemical properties

Physical state : Liquid
Color : Clear Yellow
Odor : Characteristic
Odor threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : No data available

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Boiling point : No data available
Flash point : 112 °F
Flammability (solid, gas) : Not applicable.
Vapor pressure : No data available
Relative vapor density at 20°C : No data available
Relative density : No data available
Density : 6.76 lb/gal

Density : 6.76 lb/gal Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available : No data available Auto-ignition temperature : No data available Decomposition temperature Viscosity, kinematic : No data available : No data available **Explosion limits** Particle characteristics : No data available

#### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

### **SECTION 10 Stability and reactivity**

#### 10.1. Reactivity

Flammable liquid and vapor.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11 Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Harmful in contact with skin.

Acute toxicity (inhalation) : Not classified

SureKill® Advanced Insecticide Products VAP-5™	
ATE US (oral)	1176 mg/kg body weight
ATE US (dermal)	1180.791 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

1/20/2025 (Issue date) US - en 7/13

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

Dichlorvos (62-73-7)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Kerosene (straight run) (8008-20-6)		
	Viscosity, kinematic	2.8 – 4.3 mm²/s (-20 °C, ASTM D445: Capillary viscometer)
	Symptoms/effects :	May cause drowsiness or dizziness.
	Symptoms/effects after inhalation :	None under normal conditions.

Symptoms/effects after skin contact : Harmful in contact with skin. Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : None under normal conditions.

Symptoms/effects after ingestion : Harmful if swallowed. Risk of lung edema.

## **SECTION 12 Ecological information**

#### 12.1. Ecotoxicity

Ecology - general : Very toxic to aquatic life. Hazardous to the aquatic environment, short–term : Very toxic to aquatic life.

(acute)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

Dichlorvos (62-73-7)		
LC50 - Fish [1]	0.0116 mg/l (96 h, Pimephales promelas)	
EC50 - Crustacea [1]	0.00002 mg/l (48 h, Daphnia magna)	
LC50 - Fish [2]	0.869 mg/l (96 h, Lepomis macrochirus)	
EC50 72h - Algae [1]	3.5 mg/l (Algae)	
NOEC chronic crustacea	0.0000058 mg/l	

## 12.2. Persistence and degradability

SureKill® Advanced Insecticide Products VAP-5™		
Persistence and degradability  Not rapidly degradable		
Dichlorvos (62-73-7)		
Persistence and degradability Biodegradable in the soil, Biodegradable in water.		
Kerosene (straight run) (8008-20-6)		
Persistence and degradability	Readily biodegradable in water.	

1/20/2025 (Issue date) US - en 8/13

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

#### 12.3. Bioaccumulative potential

Dichlorvos (62-73-7)	
Partition coefficient n-octanol/water (Log Pow)	1.4 – 2.03
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Kerosene (straight run) (8008-20-6)	
BCF - Other aquatic organisms [1]	207.7 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	6.23 (Estimated value, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

## 12.4. Mobility in soil

Dichlorvos (62-73-7)	
Ecology - soil	Toxic to bees.
Kerosene (straight run) (8008-20-6)	
Mobility in soil	670 – 50000 Source: HSDB
Surface tension	No data available in the literature
Ecology - soil	Low potential for adsorption in soil.

#### 12.5. Other adverse effects

Ozone : Not classified

Other adverse effects : This pesticide is toxic to aquatic organisms, including fish and invertebrates.

Fluorinated greenhouse gases : No

#### **SECTION 13 Disposal considerations**

Regional waste regulation

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information

- : Disposal must be done according to official regulations.
- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Disposal must be done according to official regulations.
- : Disposal must be done according to official regulations.
- : Flammable vapors may accumulate in the container. Do not re-use empty containers. Observe all applicable Federal, Provincial, and State regulations and local/municipal ordinances regarding disposal. Refer to product label and/or package insert for additional information. Follow label instructions.

## **SECTION 14 Transport information**

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN1268	UN1268	1268	1268
14.2. Proper Shipping Name			
Petroleum distillates, n.o.s.	PETROLEUM DISTILLATES, N.O.S.	PETROLEUM DISTILLATES, N.O.S.	Petroleum distillates, n.o.s.

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT	TDG	IMDG	IATA		
14.3. Transport hazard class(es)					
3	3	3	3		
PLAMMABLE LIQUID	3	3	3		
14.4. Packing group					
III	III	III	III		
14.5. Environmental hazards					
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes		
No supplementary information available					

#### 14.6. Transport in bulk

Not applicable

#### 14.7. Special precautions for user

DOT

UN-No. (DOT) : UN1268

DOT Special Provisions (49 CFR 172.102)

: 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter.

B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 60 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

DOT Vessel Stowage Location : A -

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

1/20/2025 (Issue date) US - en 10/13

: 220 L

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

**TDG** 

UN-No. (TDG) : UN1268

**TDG Special Provisions** : 91 - Repealed, SOR/2017-137,92 - (1) The consignor must classify these dangerous goods on

the basis of samples.

(2) The consignor must make available to the Minister, on reasonable notice given by the Minister, a document that explains the sampling method and includes the following information:

(a) the scope of the method; (b) the sampling apparatus;

(c) the sampling procedures;

(d) the frequency and conditions of sampling; and

(e) a description of the quality control management system in place, 150 - An approved ERAP is required for the dangerous goods referred to in paragraph 7.2(1)(f) of Part 7 (Emergency

Response Assistance Plan).

Explosive Limit and Limited Quantity Index : 5 L : E1 Excepted quantities (TDG) : 60 L

Passenger Carrying Road Vehicle or Passenger

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 128

**IMDG** 

Special provision (IMDG) : 223, 955 Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 Packing instructions (IMDG) : P001, LP01 IBC packing instructions (IMDG) IBC03 Tank instructions (IMDG) : T4 Tank special provisions (IMDG) TP1, TP29

: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Fire) EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER

Stowage category (IMDG) : A

Properties and observations (IMDG) : Immiscible with water.

Special provision (IATA) : A3 : E1 PCA Excepted quantities (IATA) PCA Limited quantities (IATA) : Y344 PCA limited quantity max net quantity (IATA) : 10L 355 PCA packing instructions (IATA) 60L PCA max net quantity (IATA) CAO packing instructions (IATA) 366 CAO max net quantity (IATA) 220L ERG code (IATA) 3L

## **SECTION 15 Regulatory information**

#### 15.1. Federal regulations

All components of this product are exempt or present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Dichlorvos CAS-No. 62-73-7 5 – 10%

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Dichlorvos (62-73-7)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	10 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	10 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb

FIFRA Labelling		
EPA Registration Number	47000-74	
This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label.		
FIFRA Signal Word	Danger	
FIFRA Precautionary Statement	Keep out of reach of children. Hazards to humans and domestic animals. Corrosive. Causes irreversible eye damage. Harmful if swallowed. Do not get in eyes, on skin, or on clothing.	

## 15.2. International regulations

No additional information available

## 15.3. State regulations



This product can expose you to DDVP (Dichlorvos), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

## **SECTION 16 Other information**

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) Issue date : 1/20/2025

Full text of hazard classes and H-statements	
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H330	Fatal if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life

Safety Data Sheet (SDS), USA

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.